

Environmental Protection Agency

§ 409.72

methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *gross cane* shall mean that amount of crop material as harvested, including field trash and other extraneous material.

(c) The term *net cane* shall mean that amount of "gross cane" less the weight of extraneous material.

(d) The term *x* shall mean that fraction of the "net cane" harvested by the advanced harvesting systems.

[40 FR 8504, Feb. 27, 1975]

§ 409.62 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

Effluent characteristics	Maximum for any 1 day		Average of daily values for 30 consecutive days shall not exceed	
	kg/kgk gross cane	lb/1,000 lb gross cane	kg/kgk gross cane	lb/1,000 lb gross cane
BOD5	(¹)	(¹)	(¹)	(¹)
TSS	9.9	9.9	3.6	3.6
pH	(¹)	(¹)	(¹)	(¹)

¹ No limitations.

[40 FR 8504, Feb 27, 1975, as amended at 44 FR 64080, Nov. 6, 1979; 45 FR 59152, Sept. 8, 1980; 60 FR 33950, June 29, 1995]

§ 409.67 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 409.62 of this subpart for the best practicable

control technology currently available (BPT).

[51 FR 24999, July 9, 1986]

Subpart G—Hawaiian Raw Cane Sugar Processing Subcategory

SOURCE: 40 FR 8504, Feb. 27, 1975, unless otherwise noted.

§ 409.70 Applicability; description of the Hawaiian raw cane sugar processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of sugar cane into a raw sugar product for those cane sugar factories, other than those described by subpart F, located in the State of Hawaii.

§ 409.71 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

§ 409.72 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, and subject to the provisions of paragraph (a) of this section, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT): There shall be no discharge of process waste water pollutants to navigable waters.

(a) Process waste water pollutants in the overflow may be discharged to navigable waters whenever rainfall events cause an overflow of process waste water from a facility designed, constructed, and operated to contain all process generated waste waters.

(b) [Reserved]

[40 FR 8504, Feb. 27, 1975, as amended at 60 FR 33950, June 29, 1995]